

THARMAC
Cellspin®



Cellspin®
I and II

CYTOCENTRIFUGES

FOR THE PRODUCTION OF

- » Thin-layer cell preparations
- » Monolayer cell preparations



CYTOCENTRIFUGES

Cellspin[®]

THE TOP-END PRODUCT FROM THARMAC[®]

Easy to use – reliable results

Cellspin[®] cytocentrifuges from THARMAC[®], the world market leader for cytocentrifuges made in Germany, combine fast and reliable results with exceptionally simple operation.

Is your laboratory growing? *Cellspin*[®] grows with you!

The unique Quickchange[®] system supports effective working, even with high sample volumes. Whether it be small or large volumes – *Cellspin*[®] delivers the right solution for every requirement. The large selection of consumables allows all of the samples to be processed in the same way and, thanks to the Double Cellfunnel[®] you are even able to double your sample throughput while effortlessly maintaining the same high standard of quality.

Cellspin[®] FROM THARMAC[®] – QUALITY MADE IN GERMANY



Cellspin[®] I

FLEXIBILITY & RELIABILITY – ADVANTAGES THAT IMPRESS

- » The only cytocentrifuge that grows with your laboratory's demands
- » Available as a 4, 8 and 12-position cytocentrifuge
- » Rotors can be extended at any time
- » Open and closed cytorotors for open or protected working
- » Can be used both as a cytocentrifuge and a laboratory centrifuge
- » For diagnostic purposes in human and veterinary medicine
- » Can be used in cytology, urology, microbiology, haematology, virology, oncology and many more
- » *Cellspin*[®] uses familiar monolayer filter cards
- » Suitable for volumes from 0.1 to 5 ml
- » Quickchange[®] for quick working with high sample numbers
- » Double Cellfunnel[®] to double capacity with high sample numbers
- » Temperature control for special diagnostic procedures*
- » Can be combined with Shandon[™] Cytospin[™]
- » **Quality – made in Germany**

*only *Cellspin*[®] IIR

Cellspin[®] II



CYTOCENTRIFUGES

ROTORS

CYTOCENTRIFUGATION OR SEDIMENTATION?

The rotor has the power!

Our *Cellspin® I* and *Cellspin® II* can be configured entirely according to your individual requirements. We offer you the perfect answer for every cytology question. The unique Quickchange® system allows rotors to be changed in seconds. One device, endless applications. The choice is yours!

JC101 – THE CLOSED, REMOVABLE CYTOROTOR WITH QUICKCHANGE®

- » Available as a 4, 8 and 12-position cytorotor (the picture shows the 8-position cytorotor)
- » Processes up to 24 samples simultaneously
- » Protects staff and the samples when loading, during use and when unloading (e.g. under a safety workbench)



JC101

JC370 – THE OPEN, REMOVABLE CYTOROTOR WITH QUICKCHANGE®

- » Available as a 4, 8 and 12-position cytorotor (the picture shows the 8-position cytorotor)
- » Processes up to 24 samples simultaneously
- » Rapid rotor changes allow the readying of further samples in a second rotor during preparation and therefore a significant increase in sample throughput



JC370

JC750 – THE OPEN, REMOVABLE EASY ROTOR

- » Cyt rotor especially as an supplement to the Shandon™ Cytospin™
- » Processes up to 24 samples simultaneously




JC750

JC105 – THE CLOSED, REMOVABLE EASY ROTOR

- » Cyt rotor especially as an supplement to the Shandon™ Cytospin™
- » Processes up to 24 samples simultaneously

JC380 – THE SWING-OUT ROTOR WITH QUICKCHANGE® FOR 15 ML CENTRIFUGE TUBES


- » Sedimentation rotor for up to 8 centrifuge tubes
- » Suitable for 15 ml centrifuge types ("Falcon" type)
- » With Quickchange® for a quick change between cytocentrifuge and laboratory centrifuge



JC380

JC381 – THE SWING-OUT ROTOR WITH QUICKCHANGE® FOR 50 ML CENTRIFUGE TUBES

- » Sedimentation rotor for up to 6 centrifuge tubes
- » Suitable for 50 ml centrifuge types ("Falcon" type)
- » With Quickchange® for a quick change between cytocentrifuge and laboratory centrifuge



JC381, partially with JC382

JC382 – THE ADAPTER (COMPATIBLE WITH JC381)

- » Reduction to 15 ml centrifuge tubes ("Falcon" type)

All open cytorotors are also available as fixed-installation variants!

CYTOCENTRIFUGES

TECHNICAL SPECIFICATIONS



Cellspin® I



Cellspin® II



	Cellspin® I	Cellspin® II
Sample volumes	<ul style="list-style-type: none"> » Single Cellfunnel®: 0.5 ml » Double Cellfunnel®: 2x 0.5 ml » ECOfunnel®: 5 ml 	<ul style="list-style-type: none"> » Single Cellfunnel®: 0.5 ml » Double Cellfunnel®: 2x 0.5 ml » ECOfunnel®: 5 ml
Performance	<ul style="list-style-type: none"> » 6.000 RPM* - 208-240V/50-60Hz - 115V/60Hz *with CellClip rotor/swing-out rotor up to 2,000 RPM 	<ul style="list-style-type: none"> » 15.000 RPM* - 200-240V/50-60Hz - 115V/60Hz *with CellClip rotor/swing-out rotor up to 2,000 RPM
Rotors	<ul style="list-style-type: none"> » CellClip rotors <ul style="list-style-type: none"> - Cyt rotor with 4, 8 or 12 positions - Removable or screwed-in - Open or closed » Swing-out rotors <ul style="list-style-type: none"> - Sedimentation rotor for 15 or 50 ml centrifuge tubes ("Falcon" type) 	<ul style="list-style-type: none"> » CellClip rotors <ul style="list-style-type: none"> - Cyt rotor with 4, 8 or 12 positions - Removable or screwed-in - Open or closed » Swing-out rotors <ul style="list-style-type: none"> - Sedimentation rotor for 15 or 50 ml centrifuge tubes ("Falcon" type)
Ease of operation	<ul style="list-style-type: none"> » Ergonomic operation and information panel » Simple rotor changes thanks to Quickchange® 	<ul style="list-style-type: none"> » Ergonomic operation and information panel » Simple rotor changes thanks to Quickchange® » 10 memory slots
Control	<ul style="list-style-type: none"> » Film keypad For precise, fast and simple entry of the parameters with option keys » Speed RPM d=100 RPM, from 500 RPM » Time t./min Input in minutes, up to 99 min » Pulse button for brief initial centrifugation » RCF button display of the approximate RCF during the run 	<ul style="list-style-type: none"> » Film keypad For precise, fast and simple entry of the parameters with option keys » Speed RPM or RCF d=100 RPM, from 500 RPM » Time t./min Input in minutes, up to 99 min » Pulse button for brief initial centrifugation » Toggle button RCF/RPM » Short start-up and braking times, even for rotors in the high-speed range » Selectable acceleration and deceleration in 9 stages

	<i>Cellspin® I</i> 	<i>Cellspin® II</i> 
Safety	<ul style="list-style-type: none"> » Cover locking and retainer » Imbalance shut-off » Automatic rotor detection » Emergency unlocking » IEC 1010 » Safety alarm to protect users and samples 	<ul style="list-style-type: none"> » Cover retainer » Imbalance shut-off » Automatic rotor detection » Emergency unlocking » IEC 1010 » Safety alarm to protect users and samples » Motor overheating protection » Cover fall arrester » Vessel overheating protection
Construction	<ul style="list-style-type: none"> » Metal housing and cover » Centrifuge space made from rust-free stainless steel » Clip lock Viewing window in the cover 	<ul style="list-style-type: none"> » Metal housing and cover » Centrifuge space made from rust-free stainless steel » Viewing window in the cover
Dimensions (hxwxd)	26 x 37 x 43 cm	35 x 40 x 70 cm
Weight	Approx. 25 kg	Approx. 29 kg
Temperature control <i>(nur Cellspin® IIR)</i>		<ul style="list-style-type: none"> » Infinitely controllable from -20°C to +40°C » Pre-cooling function (fast cool)

S.P.R.L	www.amlab.be info@amlab.be Tél : + 32 83 66 89 30 Fax : + 32 83 66 89 33
	